




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A01M 23/24 // 23/28	A1	(11) International Publication Number: WO 97/00607 (43) International Publication Date: 9 January 1997 (09.01.97)
(21) International Application Number: PCT/SE96/00771 (22) International Filing Date: 12 June 1996 (12.06.96) (30) Priority Data: 9502253-9 21 June 1995 (21.06.95) SE (71)(72) Applicant and Inventor: HANSSON, Göran [SE/SE]; Växjövägen 17, S-360 24 Linneryd (SE). (74) Agent: LUNDQUIST, Arne; Pionjärgatan 31, S-587 34 Linköping (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GR, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>

(54) Title: A TRAP FOR CATCHING AND KILLING OF SMALL ANIMALS

(57) Abstract

A trap for trapping and killing of small animals, like rats and mice is described. It comprises a stand (1), a pivoting clamp means, journalled in the stand around a first axis (5), which clamp means can be strained against the action of a force means (4) like a spring, and which can be released by a releasing means from a first, loaded position, when an animal acts upon the releasing means, so that the clamp means substantially immediately swings, acted upon by the force means, to a second position, where it hits and kills the animal. The clamp means, extending from the first axis (5), is provided with a first (2) and a second (3) arm. A first fastening point (8) of said force means is provided at the end, that is turned from the first axis (5) of the first arm (2), the second fastening point (9) of the force means is provided at the stand. The force line between the two fastening points of the force means runs through or in the vicinity of said first axis (5), so that the force means exerts no or just a minor torque in the direction towards the second position of the clamp means, when the clamp means is in its first position. The trap is primarily characterized in that the releasing means is journalled around the second axis (7) in the stand, forming a first arm portion designed like a cap (6) above a vessel (12) for bait, and a second arm portion (10) acting upon the first arm (2) of the clamp means when the cap (6) is lifted by the animal.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

A trap for catching and killing of small animals

The present invention relates to a trap for trapping and killing of small animals, like rats and mice, comprising a stand, a pivoting clamp means, journalled around a first axis, which clamp means can be strained against the action of a force means like a spring, and which can be released by a releasing means from a first, loaded position, when an animal acts upon the releasing means so that the clamp means substantially immediately swings, acted upon by the force means, to a second position, where it hits and kills the animal, the clamp means, extending from the first axis, being provided with a first and a second arm, a first fastening point of said force means being provided at the end, that is turned from the first axis of the first arm, the second fastening point of the force means being provided at the stand, the force line between the two fastening points of the force means running through or in the vicinity of said first axis, so that the force means exerts no or just a minor torque in the direction towards the second position of the clamp means, when the clamp means is in its first position.

Similar traps are known since a long time. They may for instance comprise a stand in the form of a plate, at which a clamp means may be stretched against the force of a screw spring, arranged around its turning axis to a loaded position, in which a lock pin keeps the clamp means at the plate. The free end of the lock pin is inserted in the loop of a locking means in the form of a movable plate, at which the bait is fixed, e g in the form of a piece of cheese.

Traps of this type have some limitations and drawbacks. It is relatively troublesome and hazardous to load such traps, and positively two hands are required. It happens frequently, that the trap hits the fingers of the user. Furthermore the animal can often remove the bait by careful action without bringing the trap to act.

The object of the present invention is thus to provide a trap of the type mentioned introductorily, which can be handled safely and that can be loaded with one single hand, and that allows the utilization of any type of bait, even liquid, and that does positively not admit the bait to be removed without bringing the trap to act.

According to the invention such a trap is characterized primarily in that the releasing means is journalled around a second axis in the stand, forming a first arm portion designed like a cap above a vessel for bait, and a second arm portion acting upon the first arm of the clamp means when the cap is lifted by the animal.

Within the scope of the invention, several embodiments are conceivable. In one suitable embodiment the second arm portion of the releasing means is provided with a locking

means, that locks the first arm of the clamp means, when said arm is in its said first position, which locking means releases the first arm of the clamp means when the cap is lifted by the animal.

In one suitable embodiment of the trap according to the invention there is provided a stop device for preventing the clamp means from being turned to let the first arm of the clamp means take a position in which the second arm portion of the releasing means cannot act upon the first arm of the clamp means.

In one further suitable embodiment there is provided guide means for guiding small animals to the bait, preventing larger animals from acting upon the releasing means.

It is advantageous to design the stand with a portion like a platform, extending backwards from the vessel. The object is that the animal shall stand with the front legs on the platform when it is in a position to be hit by the clamp means.

Advantageously the cap and the container are designed in such a way, that the bait is optically and from the smell, observable to the animal.

The invention is described in the following with one example of embodiment, which is not limiting, reference being made to the enclosed, schematical figures, of which:

Figure 1 shows a side view of one embodiment of a trap according to the invention, partly in section,

figure 2 shows a side view of an alternative embodiment of a trap according to the invention, partly in section,

figure 3 shows a side view of a trap according to the invention, with a guide means in section,

figure 4A shows a side view of the same trap, with an alternative guide means,

figure 4B shows a view of a parting wall for the guide means in figure 2A,

figure 5 shows a plan view of a trap according to the invention, partly in section.

figure 6 shows a plan view of a trap according to the invention,

figure 7 shows a view in the direction towards the container of the trap,

figure 8 shows a perspective view of an embodiment of cap with container,

figure 9 shows a perspective view of a shell for including of the trap,

figure 10 shows an alternative embodiment of a shell for including of the trap, whilst

figure 11 shows a side view of a shell, in section, for including of the trap, with a trap.

In figure 1 a plane stand is denoted by 1. A clamp means is journaled around a transversal, horizontal first axis 5. The clamp means comprises a first arm 2 and a second arm 3, both extending from said first axis 5, forming, in the trap shown, approximately a mutual right angle. In the figures the clamp means is in a first, loaded position, against the tensile force of a screw spring 4, which is fastened, partly in the outer part 8 of the first arm 2, and partly in the rear part 9 of the stand. The second arm 3 rests against a stop device 13, and the force line of the screw spring 4 runs a little, but not very much, above the first axis 5. Thereby the screw spring does not exert any turning moment on the clamp means in the direction towards the animal, that is to say against a second position, where the clamp means can hit the animal, killing it. A container 12 is provided, and covering this a cap 6, journaled around a second horizontal axis 7. The cap is connected to a second arm portion 10, which extends from the second arm 3 in such a way, that when the cap 6 is locked, the second arm portion 10 is above, and in contact with the first arm 2 of the clamp means. If now an animal lifts the cap 6, which is made easy by the design, which can be seen in figure 7, of the cap 6 and the container 12 with recesses in those parts, that are directed towards the entrance place of the animal, the second arm portion 10 will press down the first arm 2 past the neutral position of the screw spring, whereupon the screw spring exerts a quickly increasing tensile force, so that the clamp means more or less immediately hits against its second position, killing the animal. Thus the cap 6 forms, together with the second arm portion 10, a releasing means. Their design shall be such, that the bait is optically and/or from the smell, observable to the animal. In figure 8 there is shown how the container can be extended in the direction towards the animal with a portion 30, which can also be formed like a narrow slot. The animal is led by the bait in this portion or slot in the direction of the cap 6 and lifts same to get in touch with the bait under the cap.

The stop device 13 has for an object to prevent the clamp means from being inadvertently turned so that the first arm 2 gets in such a position, that the second arm portion 10 of the releasing means cannot act upon the first arm 2 of the clamp means in the intended way. It can be seen, that the stand 1 is designed with a platform 15, extending rearwards from the container 12. The object is, that the animal shall stand with its both front legs on the platform when it is in a desired position for being killed. The outer part of the second arm 3 may suitably be designed like a loop, as is seen on figures 6 and 7. Such a design facilitates the handling of the trap.

In figure 2 there is shown an alternative embodiment of the trap according to the invention. Here the second arm portion 10 of the releasing means is provided with a securing member 11, which locks the first arm of the clamp means when this is in its

said first, loaded position. The object is to prevent, that the trap is released inadvertently e.g. by a thrust from the rear on the second arm 3 of the clamp means. The securing member releases the first arm of the clamp means 2 when the cap 3 is lifted by the animal. In the trap shown the force line of the screw spring 4 runs below the first axis 5 in the first, loaded position, whereby the screw spring in this position exerts a certain but minor turning moment on the clamp means in the direction towards its second position. This turning moment thus is counteracted upon by said securing member 11.

In figure 3 there is shown in section a guide means 14 in the form of a funnel. The object of the latter is to guide animals of a desired size to the container 12 and the cap 6. In order to prevent animals to get in touch with the bait from the side, the funnel is provided with two sidewalls 31, one of which is indicated in figure 3. The funnel and the sidewalls are designed in such a way, that the clamp means with its second arm 3 has free way down to the head of the animal when the animal lifts the cap. It is important, that the guide means has a floor, in connection with the walls, so that the animal cannot enter the guide means and tilt the trap.

An alternative design of a guide means is seen in figure 4A. Here the guide means consists of a first funnel department 23, a transversal vertically displaceable cross wall 25 and a second funnel department 24 in direct connection to the trap, as has been described referring to figure 3. The cross wall 25 is provided with an opening 30, that can be adapted to animals of a desired maximum size.

In figures 9, 10 and 11 there are shown two embodiments of a shell, into which the trap can be inserted and loaded. The shell 16 in figure 9 is designed, at the front side, with a first opening 17, adapted to the desired maximum size of animals, that shall be trapped. The shell is provided with inner grooves 26, wherein the trap is inserted to a rear position, where it is snapped fixed with a snap in means 22. The shell with snap in means is suitably manufactured from plastic. The shell is, in this embodiment, provided at the upper side with a relatively small groove 18, wherein a string 19 or the like can be led to load the trap.

The embodiment of a shell, that is shown in figure 10, with reference number 27, is provided with an opening 29 of a size, that gives the maximum size of an animal to be trapped, and is provided with a relatively broad groove 28, that admits, that the trap is loaded by a finger.

Claims

1. A trap for trapping and killing of small animals, like rats and mice, comprising a stand (1), a pivoting clamp means, journalled in the stand around a first axis (5), which clamp means can be strained against the action of a force means (4) like a spring, and which can be released by a releasing means from a first, loaded position, when an animal acts upon the releasing means, so that the clamp means substantially immediately swings, acted upon by the force means, to a second position, where it hits and kills the animal, the clamp means, extending from the first axis (5), being provided with a first (2) and a second (3) arm, a first fastening point (8) of said force means being provided at the end, that is turned from the first axis (5) of the first arm (2), the second fastening point (9) of the force means being provided at the stand, the force line between the two fastening points of the force means running through or in the vicinity of said first axis (5), so that the force means exerts no or just a minor torque in the direction towards the second position of the clamp means, when the clamp means is in its first position.

characterized in that

the releasing means is journalled around a second axis (7) in the stand, forming a first arm portion designed like a cap (6) above a vessel (12) for bait, and a second arm portion (10) acting upon the first arm (2) of the clamp means when the cap (6) is lifted by the animal.

2. A trap according to claim 1,
characterized in that

the second arm portion (10) of the releasing means is provided with a securing member (11), that locks the first arm (2) of the clamp means when this is in its said first position, which securing member (11) releases the first arm (2) of the clamp member, when the cap (6) is lifted by the animal.

3. A trap according to claim 1
characterized in that

there is provided a stop device (13) for preventing the clamp means from being turned to let the first arm (2) of the clamp means take a position in which the second arm portion (10) of the releasing means cannot act upon the first arm (2) of the clamp means.

4. A trap according to claim 1,
characterized in that



there is provided guide means (14) for guiding small animals to the bait, preventing larger animals from acting upon the releasing means.

5. A trap according to claim 1, characterized in that stand is designed with a portion (15) like a platform, extending backwards from the vessel. (12)

6 A trap according to claim 1, characterized in that the cap (6) and the vessel (12) are designed in such a way, that the bait is optically and from the smell, observable to the animal.

7. A trap according to claim 1, characterized in that it is provided with an outer shell (16) into which the trap may be inserted to a protected position, which shell (16) is provided with a first opening (17), with such a size, and located in such a way, that it admits animals of a desired, maximum size access to the releasing device (6), and that the shell (16) is provided with with an elongated second opening (18) arranged in such a way, that a string (19) or the like may be led in through the second opening and releasably stretch the clamp means (3) to the first, loaded position.

1/4



2/4




FIG 3




FIG 4B




FIG 4A

3/4




FIG 5

FIG 6





FIG 7

4/4



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/00771

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A01M 23/24 // A01M 023/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 101760 A (HERBERT HADDAN & CO.), 19 October 1916 (19.10.16) --	1-7
A	NO 37719 C1 (THE MARK PATENT COMPANY LIMITED AV SOMERSET), 23 October 1920 (23.10.20) --	1-7
A	GB 2252485 A (NICHOLAS GEORGE BAILEY), 12 August 1992 (12.08.92) -- -----	7

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 Sept 1996

Date of mailing of the international search report

27-09-1996

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

THOMAS AVASALU

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

05/09/96

International application No.

PCT/SE 96/00771

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB-A-	101760	19/10/16	NONE	
NO-C1-	37719	23/10/20	NONE	
GB-A-	2252485	12/08/92	DE-D, T- 69109671 EP-A, B- 0523191	26/10/95 20/01/93

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.